

# CSE5334 DATA MINING

Lecture 9: Classification (5)

CSE4392/5334 Data Mining, Fall 2009  
Department of Computer Science and Engineering, University of Texas at Arlington  
Chengkai Li (Slides courtesy of Vipin Kumar)

## Instance-Based Classifier

### Instance-Based Classifiers

**Set of Stored Cases**

Atr1	.....	AtrN	Class
			A
			B
			B
			C
			A
			C
			B

- Store the training records
- Use training records to predict the class label of unseen cases

**Unseen Case**

Atr1	.....	AtrN

### Instance Based Classifiers

Examples:

- ▣ Rote-learner
  - ▣ Memorizes entire training data and performs classification only if attributes of record match one of the training examples exactly
- ▣ Nearest neighbor
  - ▣ Uses k "closest" points (nearest neighbors) for performing classification

### Nearest Neighbor Classifiers

Basic idea:

- ▣ If it walks like a duck, quacks like a duck, then it's probably a duck.

Training Records

Test Record

Compute Distance

Choose k of the "nearest" records

### Nearest-Neighbor Classifiers

- Requires three things
  - The set of stored records
  - Distance Metric to compute distance between records
  - The value of  $k$ , the number of nearest neighbors to retrieve
- To classify an unknown record:
  - Compute distance to other training records
  - Identify  $k$  nearest neighbors
  - Use class labels of nearest neighbors to determine the class label of unknown record (e.g., by taking majority vote)

### Definition of Nearest Neighbor

(a) 1-nearest neighbor (b) 2-nearest neighbor (c) 3-nearest neighbor

K-nearest neighbors of a record x are data points that have the k smallest distance to x

### 1 nearest-neighbor

Voronoi Diagram

### Nearest Neighbor Classification

- Compute distance between two points:
  - Euclidean distance
 
$$d(p, q) = \sqrt{\sum_i (p_i - q_i)^2}$$
- Determine the class from nearest neighbor list
  - take the majority vote of class labels among the k-nearest neighbors
  - Weigh the vote according to distance
    - weight factor,  $w = 1/d^2$

### Nearest Neighbor Classification...

- Choosing the value of k:
  - If k is too small, sensitive to noise points
  - If k is too large, neighborhood may include points from other classes

### Nearest Neighbor Classification...

- Scaling issues
  - Attributes may have to be scaled to prevent distance measures from being dominated by one of the attributes
  - Example:
    - height of a person may vary from 1.5m to 1.8m
    - weight of a person may vary from 90lb to 300lb
    - income of a person may vary from \$10K to \$1M

### Nearest Neighbor Classification...

- Problem with Euclidean measure:
  - High dimensional data
    - **curse of dimensionality**
  - Can produce counter-intuitive results

1 1 1 1 1 1 1 1 1 1 1 0	vs	1 0 0 0 0 0 0 0 0 0 0 0
0 1 1 1 1 1 1 1 1 1 1 1		0 0 0 0 0 0 0 0 0 0 0 1
$d = 1.4142$		$d = 1.4142$

◆ Solution: Normalize the vectors to unit length

### Nearest neighbor Classification...

- k-NN classifiers are **lazy learners**
  - ▣ It does not build models explicitly
  - ▣ Unlike eager learners such as decision tree induction and rule-based systems
  - ▣ Classifying unknown records are relatively expensive

### Example: PEELS

- PEELS: Parallel Exemplar-Based Learning System (Cost & Salzberg)
  - ▣ Works with both numeric and nominal features
    - For nominal features, distance between two nominal values is computed using **modified value difference metric (MVDM)**
  - ▣ Each record is assigned a weight factor
  - ▣ Number of nearest neighbor,  $k = 1$

### Example: PEELS

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Distance between nominal attribute values:

$$d(\text{Single}, \text{Married}) = |2/4 - 0/4| + |2/4 - 4/4| = 1$$

$$d(\text{Single}, \text{Divorced}) = |2/4 - 1/2| + |2/4 - 1/2| = 0$$

$$d(\text{Married}, \text{Divorced}) = |0/4 - 1/2| + |4/4 - 1/2| = 1$$

$$d(\text{Refund}=\text{Yes}, \text{Refund}=\text{No}) = |0/3 - 3/7| + |3/3 - 4/7| = 6/7$$

Class	Marital Status		
	Single	Married	Divorced
Yes	2	0	1
No	2	4	1

Class	Refund	
	Yes	No
Yes	0	3
No	3	4

$$d(V_1, V_2) = \sum_i \left| \frac{n_{1i}}{n_1} - \frac{n_{2i}}{n_2} \right|$$

### Example: PEELS

Tid	Refund	Marital Status	Taxable Income	Cheat
X	Yes	Single	125K	No
Y	No	Married	100K	No

Distance between record X and record Y:

$$\Delta(X, Y) = w_x w_y \sum_{i=1}^d d(X_i, Y_i)^2$$

where:  $w_x = \frac{\text{Number of times X is used for prediction}}{\text{Number of times X predicts correctly}}$

$w_x \approx 1$  if X makes accurate prediction most of the time

$w_x > 1$  if X is not reliable for making predictions